

**ARM[®] Cortex[®]-M
32-bit Microcontroller****NuMicro[®] Family
NUC122 Series BSP
Revision History**

The information described in this document is the exclusive intellectual property of Nuvoton Technology Corporation and shall not be reproduced without permission from Nuvoton.

Nuvoton is providing this document only for reference purposes of NuMicro microcontroller based system design. Nuvoton assumes no responsibility for errors or omissions.

All data and specifications are subject to change without notice.

For additional information or questions, please contact: Nuvoton Technology Corporation.

www.nuvoton.com

Revision 3.00.002 (Released 2015-07-24)

1. Fix the the reset vector handler to Reset_Handler of all sample codes.
2. Fix maximum USB endpoint from 8 to 6 in USB driver, because of NUC122 USB Device Endpoint number is 6 only.
3. Fix UART transmit data bug in UART_TEST_HANDLE() of UART_TxRx_Function sample code.
4. Fix FMC_Erase() ISPF flag clear to avoid ISP disable when error in FMC driver.
5. Remove APUEN enable or disable macro in FMC driver. NUC122AN doesn't support this function.
6. Remove ISPATA, VECMAP, UID, UCID from FMC driver, because they are not supported in NUC122.
7. Revise the following four macro definitions in SPI driver to avoid affecting another SPI_SS pin. SPI_SET_SS0_HIGH() SPI_SET_SS1_HIGH() SPI_SET_SS0_LOW() SPI_SET_SS1_LOW()
8. Update USB Device driver for better compatibility
9. Add USB Device Billboard sample code to show the implementation of Billboard class.
10. Add Hard_Fault_Sample to show how to implement hard fault handler.
11. Add non-block printf supporting in retarget.c
12. Add UART FIFO size constants definitions with UART driver.
13. Add new function to control systick and select systick clock source, CLK_EnableSysTick() and CLK_DisableSysTick() in CLK driver.
14. Add UART_Wakeup sample code to demonstrate how to wakeup system by UART

Revision 3.00.001 (Released 2015-01-15)

1. Update to support new driver API

Important Notice

Nuvoton Products are neither intended nor warranted for usage in systems or equipment, any malfunction or failure of which may cause loss of human life, bodily injury or severe property damage. Such applications are deemed, "Insecure Usage".

Insecure usage includes, but is not limited to: equipment for surgical implementation, atomic energy control instruments, airplane or spaceship instruments, the control or operation of dynamic, brake or safety systems designed for vehicular use, traffic signal instruments, all types of safety devices, and other applications intended to support or sustain life.

All Insecure Usage shall be made at customer's risk, and in the event that third parties lay claims to Nuvoton as a result of customer's Insecure Usage, customer shall indemnify the damages and liabilities thus incurred by Nuvoton.

*Please note that all data and specifications are subject to change without notice.
All the trademarks of products and companies mentioned in this datasheet belong to their respective owners.*